

L1692

■ Features of L1692 Series

- 16 characters × 2 lines
- STN gray type LCD is used
- 5 × 7 dot matrix + cursor
- 1/16 duty
- 5V single power supply

■ Specification

A. Mechanical Characteristics

Item	Specifications	Unit
Module size (H×V×T) (Reflective type)	122.0×44.0×11.3	mm
Module size (H×V×T) (Built-in LED backlight type)	122.0×44.0×15.8	mm
Viewing area (H×V)	99.0×24.0	mm
Character size (5×7 dot, H×V)	4.84×8.06	mm
Dot size (H×V)	0.92×1.10	mm
Dot space	0.06	mm
Center to center dimension of mounting holes (H×V)	115.0×37.0	mm
Weight (Reflective type)	50	g
Weight (Built-in LED backlight type)	65	g

H : Horizontal, V : Vertical, T : Thickness (max.)

B. Absolute Maximum Ratings

V_{SS} = 0V

Item	Symbol	Conditions	Min.	Max.	Unit
Power supply voltage	V _{DD}		-0.3	6.0	V
	V _{LC}		V _{DD} -12.0	V _{DD}	V
Input voltage	V _{IN}		-0.3	V _{DD} +0.3	V
Operating temp.	T _{opr}		0	+50	°C
Storage temp.	T _{stg}		-20	+60	°C
Storage humidity		≤48hrs	+20	+85	%RH
		≤1000hrs	+20	+65	%RH

C. Electrical Characteristics

V_{DD} = 5V±5%, V_{SS} = 0V, Ta = 0°C to 50°C

Item	Symbol	Conditions	Min.	Typ.	Max.	Unit
Power supply voltage	V _{DD}		4.75	5.00	5.25	V
	V _{DD} -V _{LC}		4.0	—	11.0	V
Input voltage*	High	V _{IH1}	2.2	—	V _{DD}	V
	Low	V _{IL1}	0	—	0.6	V
Output voltage**	High	V _{OH1}	-I _{OH} = 0.205mA	2.4	—	V
	Low	V _{OL1}	I _{OL} = 1.2mA	—	0.4	V
Current consumption	I _{DD}	Ta = 25°C V _{DD} = 5V V _{LC} = 0.25V	—	2.0	3.0	mA
	I _{LC}		—	0.4	1.0	mA
Clock oscillation frequency	f _{osc}	Resistance oscillation	140	220	300	kHz

* Applied to DB₀ ~ DB₇, E, R_W, RS

** Applied to DB₀ ~ DB₇

D. Optical Characteristics

D-1 Reflective type

Ta = 25°C, V_{opr} = 4.75V

Item	Symbol	Conditions	Min.	Typ.	Max.	Unit
Viewing angle	θ ₁	C ≥ 2.0 ∅ = 0°	—	—	-25	deg.
	θ ₂		50	—	—	
	θ ₂ - θ ₁		75	—	—	
Contrast	C	θ = 5°, ∅ = 0°	2	4	—	—
Response time (rise)	t _{on}	θ = 0° ∅ = 0°	—	180	270	ms
Response time (fall)	t _{off}		—	250	380	
Response time (rise)	t _{on}	θ = 0°, ∅ = 0° Ta = 0°C V _{opr} = 5.0V	—	400	600	ms
Response time (fall)	t _{off}		—	720	1100	

D-2 Transflective type

Ta = 25°C, V_{opr} = 4.75V, Backlight OFF

Item	Symbol	Conditions	Min.	Typ.	Max.	Unit
Viewing angle	θ ₁	C ≥ 2.0 ∅ = 0°	—	—	-20	deg.
	θ ₂		45	—	—	
	θ ₂ - θ ₁		65	—	—	
Contrast	C	θ = 5°, ∅ = 0°	2	4	—	—
Response time (rise)	t _{on}	θ = 0° ∅ = 0°	—	180	270	ms
Response time (fall)	t _{off}		—	250	380	
Response time (rise)	t _{on}	θ = 0°, ∅ = 0° Ta = 0°C V _{opr} = 5.0V	—	400	600	ms
Response time (fall)	t _{off}		—	720	1100	

E. Recommended Operating Voltage

The recommended value of (V_{opr}) for an ambient temperature is as follows.


V_{opr} = V_{DD}-V_{LC}

Temperature (°C)	0	25	50
V _{opr} (V)	5.00	4.75	4.40


■ STN Reflective type

Item	L169200J200
Mechanical Characteristics	A
Absolute Maximum Ratings	B
Electrical Characteristics	C
Optical Characteristics	D-1
Recommended Operating Voltage	E

F-1 Power Supply




F-2 Dimensions



F-3 Pin Functions


No.	Name	Function
1	VSS	GND
2	VDD	Power supply voltage +5V
3	VLc	Liquid crystal driving voltage
4	RS	L : Instruction code input, H : Data input
5	R/W	L : Data write (LCM ← MPU), H : Data read (LCM → MPU)
6	E	Enable
7	DB ₀	Data bus line
8	DB ₁	Data bus line
9	DB ₂	Data bus line
10	DB ₃	Data bus line
11	DB ₄	Data bus line
12	DB ₅	Data bus line
13	DB ₆	Data bus line
14	DB ₇	Data bus line

F-4 Block Diagram



G-5 LED Backlight

G-5-1 LED Circuit Diagram




G-5-2 Absolute Maximum Ratings

Ta = 25°C

Item	Symbol	Specifications	Unit
LED forward current consumption*	I _F	480	mA
LED reverse voltage	V _R	8	V
LED allowable dissipation	P _D	2.0	W

* LED forward current consumption and operating temperature characteristics are as follows.



G-5-3 Electrical Characteristics

Ta = 25°C

Item	Symbol	Conditions	Min.	Typ.	Max.	Unit
LED forward input voltage	V _F	I _F = 240mA	3.8	4.1	4.4	V
LED reverse current	I _R	V _R = 8V	—	—	2.4	mA

G-5-4 Optical Characteristics

Ta = 25°C

Item	Symbol	Conditions	Specifications	Unit
Surface brightness (panel upper side)	B _p	I _F = 240mA V _{opr} = 0V	4.5 min. 5 typ.	cd/m ²
LED brightness	L	I _F = 240mA	40 min. 50 typ.	cd/m ²
LED service life			50,000 typ.	h
LED color			Yellowgreen	